

TEST REPORT

of

FCC Part 15 Subpart B SDoC

☒ New Application; ☐ Class I PC; ☐ Class II PC

Product: Bluetooth 5.1 Module
Brand: Fanstel
Model: BM833AF, BM833A
Model Difference: Antenna. Please see page 5 for detail
FCC Rule Part: Part 15 B, SDoC
Applicant: Fanstel Corporation, Taipei
Address: 10F-10, No. 79, Sec. 1, Hsin Tai Wu Rd.,
Hsi-Chih, New Taipei City 221 Taiwan

Test Performed by:

International Standards Laboratory Corp.

<LT Lab.>

*Site Registration No.

BSMI: SL2-IN-E-0013; MRA TW1036; TAF: 0997

*Address:

No. 120, Lane 180, Hsin Ho Rd., Lung-Tan Dist., Tao Yuan City 325, Taiwan

*Tel : 886-3-407-1718; Fax: 886-3-407-1738

Report No.: ISL-19LR246FB

Issue Date : 2019/10/24



Test results given in this report apply only to the specific sample(s) tested and are traceable to national or international standard through calibration of the equipment and evaluating measurement uncertainty herein.

This report MUST not be used to claim product endorsement by TAF or any agency of the Government.

This test report shall not be reproduced except in full, without the written approval of International Standards Laboratory Corp.

VERIFICATION OF COMPLIANCE

Applicant: Fanstel Corporation, Taipei
Product Description: Bluetooth 5.1 Module
Brand Name: Fanstel
Model No.: BM833AF, BM833A
Model Difference: Antenna. Please see page 5 for detail
FCC Rule Part: Part 15 B, SDoC
Date of test: 2019/9/10 ~2019/9/16
Date of EUT Received: 2019/9/6

We hereby certify that:

All the tests in this report have been performed and recorded in accordance with the standards described above and performed by an independent electromagnetic compatibility consultant, International Standards Laboratory Corp.

The test results contained in this report accurately represent the measurements of the characteristics and the energy generated by sample equipment under test at the time of the test. The sample equipment tested as described in this report is in compliance with the limits of above standards.

Test By:



Date:

2019/10/24

Jason Chao / Sr. Engineer

Prepared By:



Date:

2019/10/24

Elisa Chen / Sr. Engineer

Approved By:



Date:

2019/10/24

Jerry Liu / Technical Manager

Version

Version No.	Date	Description
00	2019/10/24	Initial creation of document

Uncertainty of Measurement

Description Of Test	Uncertainty
Conducted Emission (AC power line)	2.586 dB
Field Strength of Spurious Radiation	$\leq 30\text{MHz}$: 2.96dB 30-1GHz: 4.22 dB 1-40 GHz: 4.08 dB
Conducted Power	2.412 GHz: 1.30 dB 5.805 GHz: 1.55 dB
Power Density	2.412 GHz: 1.30 dB 5.805 GHz: 1.67 dB
Frequency	0.0032%
Time	0.01%
DC Voltage	1%

Table of Contents

1.	GENERAL INFORMATION	5
1.1.	PRODUCT DESCRIPTION	5
1.2.	RELATED SUBMITTAL(S) / GRANT (S)	6
1.3.	TEST METHODOLOGY	6
1.4.	TEST FACILITY	6
1.5.	SPECIAL ACCESSORIES	6
1.6.	EQUIPMENT MODIFICATIONS	6
2.	SYSTEM TEST CONFIGURATION	7
2.1.	EUT CONFIGURATION	7
2.2.	EUT EXERCISE	7
2.3.	LIMITATION	7
2.4.	CONFIGURATION OF TESTED SYSTEM	9
3.	SUMMARY OF TEST RESULTS	10
4.	DESCRIPTION OF TEST MODES	10
5.	CONDUCTED EMISSIONS TEST	11
5.1.	TEST SETUP	11
5.2.	MEASUREMENT PROCEDURE	11
5.3.	MEASUREMENT EQUIPMENT USED:	12
5.4.	MEASUREMENT RESULT:	13
6.	RADIATED EMISSION TEST	15
6.1.	TEST SETUP	15
6.2.	MEASUREMENT PROCEDURE	17
6.3.	SPECTRUM ANALYZER CONFIGURATION (FOR THE FREQUENCIES TESTED)	17
6.4.	MEASUREMENT EQUIPMENT USED:	18
6.5.	MEASUREMENT RESULT:	19
	PHOTOGRAPHS OF SET UP	23
	PHOTOGRAPHS OF EUT	27

1. General Information

1.1. Product Description

General:

Product Name	Bluetooth 5.1 Module
Brand Name	Fanstel
Model Name	BM833AF, BM833A
Model Difference	Antenna. Please see table below for detail.
Power Supply	5Vdc from USB (JIG)
USB port	one (JIG)

Model Summaries

module	BM833A	BM833AF
Flash/RAM	192KB/24KB	192KB/24KB
Size	10.2x15x1.9mm	10.2 (15 antenna area) x 20.6 x1.9mm.
GPIO	32	32
Antenna	PCB Trace	PCB trace
Antenna Gain	0.01dBi	-0.88dBi
BT range, low interference	680 meters at 125Kbps, est.	1400 meters at 125 Kbps, est.

1.2. Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for Part15 Subpart B, is authorized under SDoC procedure.

1.3. Test Methodology

Both conducted and radiated testing were performed according to the procedures in ANSI C63.4: 2014.

1.4. Test Facility

The measurement facilities used to collect the 3m Radiated Emission and AC power line conducted data are located on the address of **International Standards Laboratory Corp.** <LT Lab.> No. 120, Lane 180, Hsin Ho Rd., Lung-Tan Dist., Tao Yuan City 325, Taiwan which are constructed and calibrated to meet the FCC requirements in documents ANSI C63.4: 2014. FCC Registration Number is: TW1036, Canada Registration Number: 4067B-3.

1.5. Special Accessories

Not available for this EUT intended for grant.

1.6. Equipment Modifications

Not available for this EUT intended for grant.

2. System Test Configuration

2.1. EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

2.2. EUT Exercise

The EUT was operated in the normal mode.

2.3. Limitation

(1) Conducted Emission

According to section 15.107(a), ICES-003 Section 6.1 Conducted Emission Limits is as following.

Frequency range MHz	Class B Limits dB (uV)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50
Note		
1.The lower limit shall apply at the transition frequencies		
2.The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.		

(2) Radiated Emission

According to section 15.109(a), ICES-003 Section 6.2 or CISPR 22 Radiated Emission Class B Limits is as following:

Frequency (MHz)	Field strength $\mu\text{V/m}$	Distance (m)	Field strength at 3m $\text{dB}\mu\text{V/m}$
30-88	100	3	40
88-216	150	3	43.5
216-960	200	3	46
Above 960	500	3	54

CISPR 22 Limit:


Frequency range MHz	Limits dBuV/m (10m)
	Quasi-peak
30 to 230	30
230 to 1000	37

Frequency range GHz	Limits dBuV/m (3m)	
	Average	Peak
1 to 3	50	70
3 to 6	54	74

Remark: 1. Emission level in dBuV/m=20 log (uV/m)
2. Measurement was performed at an antenna to the closed point of EUT distance of 3 meters.

2.4. Configuration of Tested System

Fig. 1-1 Configuration



Support Equipment Used in Tested System

Item	Equipment	Brand	Model name	Series No	Data Cable	Power Cable
1	adaptor	Apple	A1385	N/A	N/A	Shielded /0.6m
2	Smart phone	hTC	PL99110	N/A	N/A	N/A

I/O Cable Condition of EUT and Support Units

Description	Path	Cable Length	Cable Type	Connector Type
USB power cable	Adaptor USB port to JIG micro USB port	0.6M	Non-Shielded	Metal Head

Note: All the above equipment/cables were placed in worse case positions to maximize emission signals during emission test.

Grounding: Grounding was in accordance with the manufacturer's requirements and conditions for the intended use.

3. Summary of Test Results

Rules	Description of Test	Result
§15.107 CISPR 22	Conducted Emission Class B	Compliant
§15.109 CISPR 22	Radiated Emission(Below 1GHz) Class B	Compliant
§15.109 CISPR22	Radiated Emission(above 1GHz) Class B	Compliant

4. Description of test modes


This is a modular application and the EUT was stayed in normal operation mode.

Test Plan

Applicable standard		FCC 15B		
Test Configuration		Config 1	Config 2	Config 3
		EUT + Smart mobile phone	EUT + Smart mobile phone	EUT + Smart mobile phone
Operation mode		BT link(BM833E) Antenna:Ant060	BT link(BM833F)	BT link(BM833)
No.	Description			
1	Radiated emission (30M~1GHz)(above 1GHz)	Measured	Pretest	Pretest
2	Conducted emission (DC Power)	N/A	N/A	N/A
3	Conducted emission (AC Power)	Measured	N/A	N/A

5. Conducted Emissions Test

5.1. Test Setup



5.2. Measurement Procedure

The measurements are performed in a shielded room test site. The EUT was placed on non-conduction 1.0m x 1.5m table, which is 0.8 meters above an earth-grounded.

Power to the EUT was provided through the LISN which has the Impedance (50ohm/50uH) vs. Frequency Characteristic in accordance with the standard. Power to the LISNs were filtered to eliminate ambient signal interference and these filters were bonded to the ground plane. Peripheral equipment required to provide a functional system (support equipment) for EUT testing was powered from the second LISN through a ganged, metal power outlet box which is bonded to the ground plane at the LISN.

The interconnecting cables were arranged and moved to get the maximum measurement. Both the line of power cord, hot and neutral, were measured. All of the interface cables were manipulated according to ANSI C63.4 requirements.


The highest emissions were analyzed in details by operating the spectrum analyzer in fixed tuned mode to determine the nature of the emissions and to provide information which could be useful in reducing their amplitude.

5.3. Measurement Equipment Used:


Location Con02	Equipment Name	Brand	Model	S/N	Last Cal. Date	Next Cal. Date
Conduction 02	LISN 26	R&S	ENV216	102378	11/21/2018	11/21/2019
Conduction 02	LISN 23	R&S	ENV216	101477	07/31/2019	07/31/2020
Conduction 02	Conduction 02-1 Cable	WOKEN	CFD 300-NL	Conduction 02 -1	09/11/2019	09/11/2020
Conduction 02	EMI Receiver 14	ROHDE& SCHWARZ	ESCI	101034	05/31/2019	05/31/2020
Conduction 02	ISNT4 07	Teseq GmbH	ISN T400A	30449	08/02/2019	08/02/2020
Conduction 02	ISN T8 10	Teseq GmbH	ISN T800	42773	08/02/2019	08/02/2020

5.4. Measurement Result:

Operation Mode:	Config 1
-----------------	----------



No.	Frequency (MHz)	QP_R (dBuV)	AVG_R (dBuV)	Correct Factor (dB)	QP Emission (dBuV)	QP Limit (dBuV)	QP Margin (dB)	AVG Emission (dBuV)	AVG Limit (dBuV)	AVG Margin (dB)
1	0.758	12.07	5.82	9.65	21.72	56.00	-34.28	15.47	46.00	-30.53
2	0.794	10.89	6.12	9.65	20.54	56.00	-35.46	15.77	46.00	-30.23
3	1.354	6.08	3.14	9.66	15.74	56.00	-40.26	12.80	46.00	-33.20
4	4.474	11.11	5.75	9.75	20.86	56.00	-35.14	15.50	46.00	-30.50
5	5.238	9.66	4.02	9.77	19.43	60.00	-40.57	13.79	50.00	-36.21
6	11.070	6.43	1.70	9.87	16.30	60.00	-43.70	11.57	50.00	-38.43



Site: Conduction 02



Phase: N

No.	Frequency (MHz)	QP_R (dBuV)	AVG_R (dBuV)	Correct Factor (dB)	QP Emission (dBuV)	QP Limit (dBuV)	QP Margin (dB)	AVG Emission (dBuV)	AVG Limit (dBuV)
1	0.370	45.40	30.13	9.69	55.09	79.00	-23.91	39.82	66.00
2	0.382	47.81	31.13	9.69	57.50	79.00	-21.50	40.82	66.00
3	0.394	48.58	31.10	9.69	58.27	79.00	-20.73	40.79	66.00
4	0.402	48.70	30.25	9.69	58.39	79.00	-20.61	39.94	66.00
5	0.514	37.70	21.54	9.70	47.40	73.00	-25.60	31.24	60.00
6	0.570	39.82	22.10	9.71	49.53	73.00	-23.47	31.81	60.00
7	0.630	44.56	29.95	9.71	54.27	73.00	-18.73	39.66	60.00
8	0.642	42.78	27.20	9.71	52.49	73.00	-20.51	36.91	60.00

Nc

6. Radiated Emission Test

6.1. Test Setup



The 3dB beam width of the horn antenna used for the test is as shown in the table below.

1GHz~18GHz

Frequency GHz	E-plane	H-plane	$\theta_{3dB}(\text{min})$	d = 3 m
				w (m)
1	88°	147°	88°	5.79
2	68°	119°	68°	4.04
3	73°	92°	73°	4.44
4	70°	89°	70°	4.20
5	55°	60°	55°	3.12
6	63°	62°	62°	3.60
7	48°	49°	48°	2.67
8	39°	46°	39°	2.12
9	32°	42°	32°	1.72
10	30°	39	30°	1.61

Frequency GHz	E-plane	H-plane	$\theta_{3\text{dB}}(\text{min})$	d = 3 m
				w (m)
11	32°	35°	32°	1.72
12	35°	32°	35°	1.89
13	34°	31°	31°	1.66
14	32°	27°	27°	1.44
15	36°	26°	26°	1.39
16	40°	28°	28°	1.50
17	43°	26°	26°	1.39
18	41°	22°	22°	1.17

18 GHz~26.5 GHz

Frequency GHz	E-plane	H-plane	$\theta_{3\text{dB}}(\text{min})$	d = 1 m	d = 3 m
				w (m)	w (m)
18	11.4°	12.7°	11.4°	0.199	0.598
19	10.9°	12.4°	10.9°	0.190	0.572
20	10.8°	12.4°	10.8°	0.189	0.567
21	9.8°	12°	9.8°	0.171	0.514
22	9.7°	11°	9.7°	0.169	0.509
23	10°	11.8°	10°	0.174	0.524
24	9°	11°	9°	0.157	0.472
25	10°	12.3°	10°	0.174	0.524
26	9.9°	11.1°	9.9°	0.173	0.519
26.5	9.4°	11.3°	9.4°	0.164	0.493

26 GHz~40 GHz

Frequency GHz	E-plane	H-plane	$\theta_{3\text{dB}}(\text{min})$	d = 1 m	d = 3 m
				w (m)	w (m)
26	12°	12.2°	12°	0.210	0.631
27	13°	10.5°	10.5°	0.184	0.551
28	13.2°	12.3°	12.3°	0.216	0.647
29	11.5°	12.8°	11.5°	0.201	0.604
30	12°	8°	8°	0.140	0.420
31	11.5°	10.1°	10.1°	0.177	0.530
32	11.8°	10°	10°	0.175	0.525
33	11.8°	9.5°	9.5°	0.166	0.499
34	11.6°	10°	10°	0.175	0.525
35	10.9°	9.8°	9.8°	0.171	0.514
36	11.8°	8.6°	8.6°	0.150	0.451
37	12.9°	10.5°	10.5°	0.184	0.551
38	12°	10.3°	10.3°	0.180	0.541
39	11.8°	9.8°	9.8°	0.171	0.514
40	12.5°	11.2°	11.2°	0.196	0.588

6.2. Measurement Procedure

The radiated emissions test will then be repeated on the open site or chamber to measure the amplitudes accurately and without the multiple reflections existing in the shielded room. The EUT and support equipment are set up on the turntable of one of 10 meter open field sites or 10 meter chamber. Desktop EUT are set up on a wooden stand 0.8 meter above the ground or floor-standing arrangement shall be placed on the horizontal ground reference plane. The test volume for a height of up to 30 cm may be obstructed by absorber placed on the ground plane.

For the initial measurements, the receiving antenna is varied from 1-4 meter height and is changed in the vertical plane from vertical to horizontal polarization at each frequency. The highest emissions between 30 MHz to 1000 MHz were analyzed in details by operating the spectrum analyzer and/or EMI receiver in quasi-peak mode to determine the precise amplitude of the emissions. The highest emissions between 1 GHz to 40 GHz were analyzed in details by operating the spectrum analyzer in peak and average mode to determine the precise amplitude of the emissions.

Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the antenna in the cone of radiation from that area and pointed at the area both in azimuth and elevation, with polarization oriented for maximum response. At the highest amplitudes observed, the EUT is rotated in the horizontal plane while changing the antenna polarization in the vertical plane to maximize the reading. The interconnecting cables were arranged and moved to get the maximum measurement. Once the maximum reading is obtained, the antenna elevation and polarization will be varied between specified limits to maximize the readings. All of the interface cables were manipulated according to ANSI C63.4 requirements.

The highest internal source of the EUT is defined as the highest frequency generated or used within the EUT or on which the EUT operates or tunes. If the highest frequency of the internal sources of the EUT is less than 108 MHz, the measurement shall only be made up to 1 GHz. If the highest frequency of the internal sources of the EUT is between 108 MHz and 500 MHz, the measurement shall only be made up to 2 GHz. If the highest frequency of the internal sources of the EUT is between 500 MHz and 1 GHz, the measurement shall only be made up to 5 GHz. If the highest frequency of the internal sources of the EUT is above 1 GHz, the measurement shall be made up to 5 times the highest frequency or 40 GHz, whichever is less.

6.3. Spectrum Analyzer Configuration (for the frequencies tested)

Frequency Range:	30MHz--1000MHz
Detector Function:	Quasi-Peak Mode
Resolution Bandwidth:	120kHz

Frequency Range:	Above 1000MHz
Detector Function:	Peak/Average Mode
Resolution Bandwidth:	1MHz


6.4. Measurement Equipment Used:

Location Chamber02	Equipment Name	Brand	Model	S/N	Last Date	Cal. Next Date	Cal.
Radiation (Chamber02)	BILOG Antenna 17	Schwarzbeck	Schwarzbeck VULB 9168+EMCI-N-6- 05	645	03/06/2019	03/06/2020	
Radiation (Chamber02)	Preamplifier 25	EMCI	EMC9135	980295	02/27/2019	02/27/2020	
Radiation (Chamber02)	Coaxial Cable Chmb 02-10M-02	EMC	RG214U	Chmb 02-10M-02	09/16/2019	09/16/2020	
Radiation (Chamber02)	EMI Receiver 12	ROHDE & SCHWARZ	ESCI	100804	08/30/2019	08/30/2020	

Chamber 19(966)					
Equipment Type	Manufacturer	Model Number	Serial Number	Last Cal.	Cal. Due.
966 Chamber	Chance Most	Chamber 19	N/A	08/13/2019	08/12/2020
Spectrum analyzer	R&S	FSP40	100116	01/10/2019	01/09/2020
EMI Receiver	R&S	ESR3	102461	08/08/2018	08/07/2020
Loop Antenna(9K-30M)	EM	EM-6879	271	05/31/2019	05/30/2020
Bilog Antenna (30M-1G)	SCHWARZBECK	VULB9168 w 5dB Att	736	01/29/2019	01/28/2020
Horn antenna (1G-18G)	SCHWARZBECK	9120D	9120D-1627	06/17/2019	06/16/2020
Horn antenna (18G-26G)	Com-power	AH-826	081001	11/21/2017	11/20/2019
Horn antenna (26G-40G)	Com-power	AH-640	100A	03/29/2019	03/28/2021
Preamplifier (9k-1000M)	HP	8447F	3113A06362	01/14/2019	01/13/2020
Preamplifier(1G-26G)	Agilent	8449B	3008A02471	10/29/2018	10/28/2019
Preamplifier (26G-40G)	MITEQ	JS4-26004000-27 -5A	818471	05/06/2019	05/05/2020
RF Cable (9k-18G)	HUBER SUHNER	SUCOFLEX 104A	MY1397/4A	01/17/2019	01/16/2020
RF cable (18G~40G)	HUBER SUHNER	Sucoflex 102	27963/2&37421 /2	11/12/2018	11/11/2019
Turn Table	MF	Turn Table-19	Turn Table-19	N/A	N/A
Mast Tower	MF	JSDES-15A	1308283	N/A	N/A
Controller	MF	MF-7802BS	MF780208460	N/A	N/A
AC power source	T-Power	TFC-1005	40006471	N/A	N/A
Signal Generator	Anritsu	MG3692A	20311	01/09/2019	01/08/2020
2.4G Filter	Micro-Tronics	Brm50702	76	12/25/2018	12/24/2019

6.5. Measurement Result:

Operation Mode	Config 1
----------------	----------



Mk.	Frequency (MHz)	RX_R (dBuV)	Correct Factor(dB/m)	Emission (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Ant.Pos (cm)	Tab.Pos (deg.)	Detector
1	44.55	36.10	-17.22	18.88	30.00	-11.12	200	204	peak
2	152.22	33.23	-16.00	17.23	30.00	-12.77	100	279	peak
3	737.13	32.45	-5.33	27.12	37.00	-9.88	100	0	peak
4	746.83	32.92	-5.03	27.89	37.00	-9.11	100	3	peak
5	919.49	30.13	-2.86	27.27	37.00	-9.73	200	303	peak
6	977.69	30.00	-2.00	28.00	37.00	-9.00	100	333	peak

* Note:

Margin = Emission – Limit

Emission = Radiated Amplitude + Correct Factor


Correct Factor = Antenna Correction Factor + Cable Loss – Pre-Amplifier Gain

Margin = Emission – Limit

Measurement Distance: 10 meters

The CISPR 22 limits would be applied to all FCC Part 15 devices.

Below 1GHz test, if the peak measured value meets the QP limit, it is unnecessary to perform the QP measurement.



Condition: FCC CLASS B 3M PK 3m VERTICAL
Site : Chamber 19

Operator : jason

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark	Pol/Phase
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		
1	3091.00	49.45	-14.46	34.99	74.00	-39.01	Peak	VERTICAL
2	4179.00	47.23	-11.54	35.69	74.00	-38.31	Peak	VERTICAL
3	5284.00	52.95	-8.24	44.71	74.00	-29.29	Peak	VERTICAL
4	5624.00	47.05	-7.30	39.75	74.00	-34.25	Peak	VERTICAL
5	6270.00	45.59	-5.07	40.52	74.00	-33.48	Peak	VERTICAL
6	7120.00	47.11	-2.27	44.84	74.00	-29.16	Peak	VERTICAL

* Note:

Margin = Emission – Limit

Emission = Radiated Amplitude + Correct Factor

Correct Factor = Antenna Correction Factor + Cable Loss – Pre-Amplifier Gain

Margin = Emission – Limit

Measurement Distance: Distance: 3 meters


Above 1GHz test, if the peak measured value meets the average limit, it is unnecessary to perform the average measurement.

No signal can be detected from 18GHz to 25GHz, so the graphs are omitted above 18GHz

Operation Mode	Config 1
----------------	----------

Radiated Emission Measurement
Date: 2019/9/16

Operator: Kevin Chan
Temperature: 26 °C
Humidity: 60 %



Site : Chamber 02

Polarization: Vertical

Mk.	Frequency (MHz)	RX_R (dBuV)	Correct Factor(dB/m)	Emission (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Ant.Pos (cm)	Tab.Pos (deg.)	Detector
1	41.64	36.32	-17.52	18.80	30.00	-11.20			peak
2	154.16	32.88	-15.94	16.94	30.00	-13.06			peak
3	671.17	31.02	-6.81	24.21	37.00	-12.79			peak
4	730.34	33.54	-5.59	27.95	37.00	-9.05			peak
5	880.69	30.82	-3.56	27.26	37.00	-9.74			peak
6	991.27	30.61	-1.91	28.70	37.00	-8.30			peak

* Note:

Margin = Emission – Limit

Emission = Radiated Amplitude + Correct Factor


Correct Factor = Antenna Correction Factor + Cable Loss – Pre-Amplifier Gain

Margin = Emission – Limit

Measurement Distance: 10 meters

The CISPR 22 limits would be applied to all FCC Part 15 devices.

Below 1GHz test, if the peak measured value meets the QP limit, it is unnecessary to perform the QP measurement.



Condition: FCC CLASS B 3M PK 3m HORIZONTAL
Site : Chamber 19

Operator : jason

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark	Pol/Phase
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		
1	2258.00	49.62	-15.75	33.87	74.00	-40.13	Peak	HORIZONTAL
2	3108.00	49.28	-14.43	34.85	74.00	-39.15	Peak	HORIZONTAL
3	4961.00	53.62	-9.00	44.62	74.00	-29.38	Peak	HORIZONTAL
4	5845.00	46.60	-6.53	40.07	74.00	-33.93	Peak	HORIZONTAL
5	6117.00	46.83	-5.63	41.20	74.00	-32.80	Peak	HORIZONTAL
6	6933.00	46.54	-3.25	43.29	74.00	-30.71	Peak	HORIZONTAL

* Note:

Margin = Emission – Limit

Emission = Radiated Amplitude + Correct Factor

Correct Factor = Antenna Correction Factor + Cable Loss – Pre-Amplifier Gain

Margin = Emission – Limit

Measurement Distance: 3 meters



Above 1GHz test, if the peak measured value meets the average limit, it is unnecessary to perform the average measurement.

No signal can be detected from 18GHz to 25GHz, so the graphs are omitted above 18GHz


Appendix 1

Photographs of Set Up

RADIATED EMISSION TEST (under 1GHz) (Config 1)




RADIATED EMISSION TEST (above 1GHz) (Config 1)



AC POWER LINE CONDUCTED EMISSION TEST


Config 1



Appendix 2

Photographs of EUT

EUT 1



EUT 2 BM833A



EUT 3 BM833AF



EUT 4 BM833A



EUT 5 BM833AF



~ End of Report ~